

DUPLEX 1500 to 9000

MultiEco-N Rooftop

All-purpose ventilation units
with counterflow heat exchangers

DUPLEX 1500-9000 MultiEco-N is a new generation of all-purpose ventilation units with counterflow heat recovery exchangers.

The rooftop version of DUPLEX 1500-9000 MultiEco-N compact units are used for comfort ventilation, hot-air heating and cooling in small facilities, shop floors, stores, schools, restaurants, shops, sports and industrial halls.

They are suitable wherever efficient ventilation and possibly hot-air circulation ventilation and cooling must be provided at minimum running cost, i.e. the highest efficiency of heat recovery, low power input of fans and as little noise as possible. DUPLEX MultiEco-N units are produced in compact (1500 to 6500 MultiEco-N) and semi-compact (7500 to 9000 MultiEco-N) version and contain two independently controlled EC fans with backward curved blades, a heat recovery exchanger with large heat-transfer surface and high efficiency, slide-out supply and exhaust air class G4, M5 or F7 filters, drain pans and possibly also an a circulation damper with a servo drive or integrated air heaters and coolers.

Unit casing is divided into two versions:

DUPLEX 1500-6500 MultiEco-N are frame construction, casing is made of painted metal sheet with 30 mm PIR insulation with heat transfer coefficient ($\lambda = 0,024 \text{ W/mK}$).

DUPLEX 7500-9000 MultiEco-N are frame construction, casing is made of painted metal sheet with 45 mm mineral wool insulation with heat transfer coefficient ($\lambda = 0,037 \text{ W/mK}$).

DUPLEX MultiEco-N ventilation units meet the requirements of the most stringent European standards:

- Casing properties according to EN 1886
- EC motors according to ErP 2015
- $\text{SFP} < 0,45 \text{ W}/(\text{m}^3/\text{h})$ according to PassivHaus*
- Hygienic requests according to VDI 6022
- Commission regulation (EU) requirements No. 1253/2014 (Ecodesign)


Advantages of DUPLEX MultiEco-N units:

- New design of ventilation units with excellent parameters
- Great thermal insulation of the casing (class T2)
- Reduced thermal idging (class TB2)
- Filter side changing
- Elegant and efficient connections through the roof
- Compact dimensions
- Ease of installation
- Variable configuration of discharge ports
- Unified dimensions of ports
- Optional versions with a bypass and circulation damper
- High efficiency fans - $\text{SFP} < 0,45 \text{ W}/(\text{m}^3/\text{h})^*$
- High heat recovery efficiency of the counterflow heat exchanger - up to 93 %
- Recessed junction box
- Integrated control system including temperature sensors
- Integrated web server
- Comprehensive design software

*in the defined working area




1500 to 9000 MultiEco-N




AVAILABLE MODIFICATIONS (CAN BE COMBINED)

- | | | | |
|-----|----------------------------------|-------|-----------------------------------|
| - B | with built-in bypass damper | - PT | with built-in preheater |
| - C | with built-in circulation damper | - CHF | with built-in direct chiller |
| - E | with built-in electrical heater | - CHW | with built-in water-based chiller |
| - T | with built-in hot-water heater | | |


OPERATING MODES OF DUPLEX MULTIECO-N UNITS



Ventilation with heat recovery with heating, cooling and preheating



Circulation heating or cooling



Ventilation without heat recovery (via bypass)

- ➔ e₁ ... Fresh outdoor air suction
- ➔ e₂ ... Fresh filtered air outlet
- ➔ i₁ ... Exhaust air suction
- ➔ i₂ ... Exhaust air outlet

- T, PT/É ... Central heating / electrical heater connection
- CH ... Cooling connection

SELECTION SOFTWARE



For the detailed design of DUPLEX series units, accessories and control systems we recommend using our dedicated design software. You can find it on our website at www.atrea.eu or request a CD at our office.



UNIT VENTILATORS & HEAT RECOVERY

ATREA s.r.o., Čs. armády 32
466 05 Jablonec n. N.
Czech Republic



www.atrea.eu

Phone: +420 483 368 111
Fax: +420 483 368 112
E-mail: atrea@atrea.cz

PERFORMANCE GRAPHS

DUPLEX MULTIECO-N

DUPLEX MultiEco-N		1500	2500	3500	4500	5500	6500	7500	9000
Supply air - max. ¹⁾	m ³ h ⁻¹	2 500	3 600	4 700	5 900	7 600	7 800	8 600	11 500
Extraction air - max. ¹⁾	m ³ h ⁻¹	2 300	3 650	4 600	5 750	7 650	7 900	8 300	11 300
Max. airflow according to ErP 2018 ⁵⁾	m ³ h ⁻¹	1 950	2 900	3 200	4 550	5 350	5 750	7 100	8 000
Heat recovery efficiency ²⁾	%	up to 93 %							
Number of versions and positions	-	see table „Mounting positions“, page 4							
Weight ³⁾	kg	290-350	350-420	405-480	460-560	520-630	630-750	1 170-1 310	1 260-1 400
Max. power input	kW	1,5	2,5	4,4	4,4	6,5	6,5	6,6	8,9
Voltage	V	230	400	400	400	400	400	400	400
Frequency	Hz	50							
Revolutions	min ⁻¹	2 920	3 000	2 980	2 980	2 700	2 700	2 700	2 570
Heating output E low - max. ⁵⁾	kW	2,1	4,2	7,2	7,2	9,9	9,9	-	-
Heating output E high - max. ⁵⁾	kW	4,2	8,4	10,8	12,6	14,7	14,7	-	-
Heating output T - max. ⁴⁾	kW	18	27	36	46	67	75	85	90
Cooling output CHW - max. ⁴⁾	kW	9	12	22	30	39	46	67	72
Cooling output CHF - max. ⁴⁾	kW	10	13	25	37	41	50	55	60

¹⁾ Maximum flow rate through units at zero external pressure


²⁾ According to air volume

³⁾ Depending on equipment


⁴⁾ Depending on register type, liquid and flow rates

⁵⁾ For detailed information please use our DUPLEX selection software.


PERFORMANCE SUMMARY



HEAT RECOVERY EFFICIENCY




HEATING AND COOLING PERFORMANCES




BASIC DIMENSIONS

1500-6500 MultiEco-N
configuration 4/16




7500-9000 MultiEco-N
configuration 10/0




* dimension only for DUPLEX 9000 MultiEco-N

BASE FRAME (optional accessory)


1500-6500 MultiEco-N



For position 4 / x




For position 3 / x



DUPLEX Multi-N		1500	2500	3500	4500	5500	6500	7500	9000
Dimension H	mm	1 605	1 605	1 605	1 605	1 605	1 700	1 795	1 795
Dimension B	mm	555	685	770	990	1 170	1 390	1 620	1 620
Length L	mm	2 560	2 560	2 560	2 560	2 560	2 650	3 370	3 370
Dimension N	mm	130	105	105	105	105	105	-	-
Dimension U	mm	270	105	105	105	105	105	-	-
Dimension P	mm	135	105	105	105	105	105	-	-
Dimension J	mm	100	100	165	225	315	340	-	-
Dimension M	mm	155	185	205	265	355	350	-	-
Condensate drain	mm	ø 32							
Connecting ports									
Dimension X x Y	mm	300 x 300	400 x 400	400 x 400	500 x 500	500 x 500	700 x 500	900 x 710	900 x 710
Base frame									
Dimension D	mm	2 500	2 500	2 500	2 500	2 500	2 590	-	-
Dimension F	mm	1 545	1 545	1 545	1 545	1 545	1 640	-	-
Dimension E	mm	1 228	1 228	1 228	1 228	1 228	1 273	-	-
Dimension G (between anchoring holes)	mm	1 505	1 505	1 505	1 505	1 505	1 600	-	-
Dimension S	mm	795	595	595	395	395	490	-	-
Dimension Q	mm	400	300	300	200	200	278	-	-
Dimension T	mm	470	370	370	270	270	287	-	-

Note: For detailed design and technical data we recommend using our dedicated selection software.

TYPES AND DIMENSIONS OF CONNECTING PORTS



INSTALLATION AND VERSIONS OF DUPLEX MULTIECO-N



INSTALLATION VERSIONS AND CONNECTING PORTS

DUPLEX 1500 to 9000 MultiEco-N units are available in a range of versions to facilitate their installation on the roof (outside). Rooftop units enable to go through the roof which is an excellent solution that saves material and labour costs in ducting and also significantly saves the energy lost

Detailed drawings are shown in the summary table "Mounting positions". DUPLEX units are characterised by a wide range of accessories - the ports may be optionally fitted with flexible flanges, duct extensions or special hoods if required.



MOUNTING POSITIONS AND PORT CONFIGURATION

DUPLEX 1500-6500 MultiEco-N




* DUPLEX 3500-6500 MultiEco-N with max. one coil

DUPLEX 7500-9000 MultiEco-N



MOUNTING POSITIONS - CONNECTIONS THROUGH THE ROOF





HANDLING SPACE

DUPLEX units must be installed with the prescribed handling space around the unit in mind. Below the unit at least 150 mm must be left to install the DN 32

condensate drain line. This line must run through a U-bend at least 150 mm high into a sewer. Handling space in front of the unit must be maintained for replacing filters.

1500-6500 MultiEco-N




* only for units with built-in coil

handling space in front of the door
wall

control manifolds
wall

control module



7500-9000 MultiEco-N

Type	T (mm)
DUPLEX 1500 MultiEco-N	600
DUPLEX 2500 MultiEco-N	700
DUPLEX 3500 MultiEco-N	800
DUPLEX 4500 MultiEco-N	1 000
DUPLEX 5500 MultiEco-N	1 200
DUPLEX 6500 MultiEco-N	1 400
DUPLEX 7500 MultiEco-N	1 600
DUPLEX 9000 MultiEco-N	1 600

ACOUSTIC POWER L_w AND ACOUSTIC PRESSURE $L_{D,3}$

Type	Working point	Acoustic power L_w [dB(A)]					Acoustic pressure $L_{D,3}$ [dB(A)] at distance of 3 m
		inlet e_1	inlet i_1	outlet e_2	outlet i_2	unit	
DUPLEX 1500 MultiEco-N	1 500 m ³ /h (200 Pa)	57	57	87	87	60	40
DUPLEX 2500 MultiEco-N	2 500 m ³ /h (200 Pa)	57	57	82	82	61	40
DUPLEX 3500 MultiEco-N	3 500 m ³ /h (200 Pa)	58	59	87	88	59	38
DUPLEX 4500 MultiEco-N	4 500 m ³ /h (200 Pa)	65	65	90	90	61	40
DUPLEX 5500 MultiEco-N	5 000 m ³ /h (200 Pa)	67	67	96	95	51	31
DUPLEX 6500 MultiEco-N	6 000 m ³ /h (200 Pa)	66	68	96	88	65	44
DUPLEX 7500 MultiEco-N	7 500 m ³ /h (200 Pa)	65	69	91	92	73	51
DUPLEX 9000 MultiEco-N	8 500 m ³ /h (200 Pa)	67	66	97	97	76	46

MODIFICATIONS

DUPLEX MULTIECO-N - BASIC UNIT

DUPLEX xxxx MultiEco-N



Basic configuration

DUPLEX 1500-6500 MultiEco-N

The compact unit consists of supply and exhaust fans in semispiral casing with anti-vibration mounting, removable counterflow air-to-air heat recovery core assembled from thin plastic plates, removable G4, M5 or F7 supply and exhaust air filters, and a condensate pan with DN 32 flexible hose. Top doors enable easy access to all built-in components. Front doors for easy filters changing.

DUPLEX 7500-9000 MultiEco-N

The unit consists of 3 separate sections:

- 1 - supply free-wheel fan with electric motors in anti-vibration mounting, removable supply filter G4, M5 or F7
 - 2 - cross-flow heat recovery exchanger with an electric motor; a belt pulley and a belt
 - 3 - exhaust free-wheel fan with electric motors in anti-vibration mounting, removable exhaust filter G4, M5 or F7
- A front door enables easy access to all built-in components and filters.

The units meet requirement in accordance with Commission regulation (EU) No. 1253/2014 (Ecodesign) in the defined working area.



Fans

All units are equipped with high-efficiency fans (ebm-papst and Ziehl Abegg) with free-running impellers and backward curved blades. Whole range of DUPLEX 1500 to 9000 MultiEco-N fans meets the requirements of the European directive ErP 2015.

Me.xxx; Mi.xxx



Heat recovery exchanger

The only heat recovery core type made of plastic in counterflow arrangement with high efficiency - up to 93 %.

S7.C


DUPLEX MULTIECO-N - MODIFICATION DESCRIPTION



By-pass („B“)

By-pass of the plate heat recovery core on supply air side. By-pass consists of an opposed-blade damper and an actuator. It is fitted next to the recovery core inside the unit; it does not increase size of the unit. The standard actuator is BELIMO 24 V; other types are available upon request.

B.x



Mixing damper („C“)

The mixing damper is used to mix exhaust and supply air. Circulation valve consists of an opposed-blade damper and actuator. It is fitted next to the recovery core inside the unit; it does not increase the size of the unit. The standard actuator is BELIMO 24 V; other types are available upon request.


C.x



Hot water heating coil („T“)

Built-in water-to-air three-row (possibly five-row) heating coil; made of copper pipes and aluminum fins. Designed for systems up to 110 °C and 1,0 MPa. The coil is standardly equipped with flexible connection and a steam-gas capillary thermostat for freeze protection. Units in modification T (with heating coil) must be equipped with e, supply air shutoff damper; an actuator with spring-return function is recommended. A coil hydraulic kit for heating capacity control of RE-TPO4 or RE-TPO3 type can be supplied with the coil upon request. Due to roof installation we strictly recommend to use non-freezing liquid.


T.x



Electric heating coil („E“)

Integrated electric heating coils consist of PTC (Positive Temperature Coefficient) cells; they are generally used to heat up supply air. By default, electric heating coils always include protective thermostats (operational as well as emergency with manual reset) and regulation module KM featuring power switching elements with so called "zero" switching function (SSR). Built-in electric heating coils are offered in the 1500-6500 MultiEco-N units in two power options (basic and powerful). For more information please refer to the selection software DUPLEX.


E.x



Direct expansion (DX) coil („CHF“)

A built-in coil made of copper pipes and aluminum fins, including a condensate pan with individual condensate drainage and a pressure switch for freeze alarm. Three- or four-row coils with various evaporate temperature are chosen depending on capacity required, refrigerant type and air parameters. Optionally it is possible to deliver double-circuit evaporator in division 1:1 or 1:2, or completely atypical with needed capacity.

CHF.x



Chilled water cooling coil („CHW“)

A built-in coil made of copper pipes and aluminum fins, including a condensate pan with individual condensate drainage. Three- or five-row coils are chosen depending on capacity required, cooling medium type and air parameters. The cooling coil can be equipped with the R-CHW2 or R-CHW3 hydraulic kit on request.

CHW.x



Integrated pre-heater („PT“)

Built-in water-to-air three-row heating coil; made of copper pipes and aluminum fins. Designed for systems up to 110 °C and 1,0 MPa. Non-freezing liquid must be used.

PT.x

OTHER OPTIONAL ACCESSORIES (BASIC OVERVIEW)

Ke.xxx; Ki.xxx

Shutoff damper e₁; i₁



Shutoff dampers standardly fitted with BELIMO actuators are located in the air inlet port. The following damper types are available:

- fresh air damper e₁ - mandatory for C modification (with mixing damper) and T, PT modification (with heating coil)
- exhaust air damper i₁

Fe.xxx; Fi.xxx

Air filtration



All DUPLEX MultiEco-N units can be equipped with supply or exhaust air filtration of M5 or F7 class instead of standard G4 class. Pressure drop of the filter is then 50 to 100 Pa (clean filter) depending on air flow rate, unit type and dirt accumulated.

RE-TPO.x

Heating coil hydraulic kit



Its function is to control heating capacity of a heating coil. It consists of a three-speed pump, two globe shutoff valves and connection pipes. Further equipment depends on the type:

- RE-TPO4 - four-way mixing valve with an actuator for digital control system
- RE-TPO3 - three-way mixing valve with an actuator for digital control system

R-CHW.x

Cooling coil hydraulic kit



Its function is to control cooling capacity of a chilled-water cooling coil. It always consists of two globe shutoff valves and connection pipes. Further equipment depends on the type:

- R-CHW3 - three-way mixing valve with an actuator
- R-CHW2 - throttling valve with an actuator for digital control system

Hot water heating coil (TPO)



Separately supplied coil for installation into round duct. It is suitable for cramped locations, where it is impossible to put the coil inside the unit, as well as for rooftop units. The coil is standardly equipped with the steam-gas capillary thermostat.

Electric heating coil (EPO-V)



Separately supplied heating coil to be fitted into round or rectangular duct. Capacities and diameters can be found in respective catalogue sheets.

FK.x

Spare cartridge filters



Replacement filter cartridges in different sizes based on the unit type. Available in F5 and F7 filtration class.

H.P


Flexible connections



Ports can be equipped with flexible connections upon request.

CF.XXX

Constant air flow and pressure



Manometers reading fan pressure together with controls, enables intelligent fan control of preselected airflow. This accessory assumes the unit is equipped with digital controls of RD5 type. Using a second manometer (optional accessory) in the supply air duct enables the user to control constant pressure in the supply duct.


Duct extension



Rectangular duct extension for connection through the roof. Standard length is 1 m.


MFF

Tube manometers



Accessory for filters for simple view of current pressure drop. The tube manometers are obligatory for hygienic unit design in accordance with the VDI 6022.

Base frame



Dismountable base frame with integrated PIR (30 mm) insulation and service doors. Standard height 500 mm, others on request. Available only for DUPLEX 1500-6500 Multi-N Rooftop.

Feets



The MultiEco-N units can be equipped with an adjustable feet (alternative to base frame).

Special hoods



Special weatherproof hoods for inlet (e₁) and outlet (i₂) ports. The hood for e₁ port in combine with integrated droplet eliminator.

CONTROLS






DUPLEX MultiEco-N units are delivered with basic control components or with complete control systems.

There are three types of control systems available (Basic, CPM and RD5) according to customer needs and an application. The systems also include variety of sensors (temperature, humidity, air quality, CO₂) for effective operation control.

Features of the control systems

- selection of the most suitable and efficient control system at the lowest cost, depending on the particular application
- control system is integrated with the unit, most components are already wired and checked in factory, thus reducing the risk of incorrect wiring
- no control system project documentation is necessary for standard cases, standardized solutions can be used
- simple wiring, system simplicity, error indication
- qualified technical support and consulting

SUMMARY OF DUPLEX MULTIECO-N CONTROL SYSTEMS

Type	Use	Controller
Basic	<ul style="list-style-type: none"> - all electrical components are wired to a junction box terminal strip inside or outside the unit - standard components are fans, damper actuators, capillary freeze protection thermostat of hot water heating coil - more components is included upon customer's request (exact actuator type, sensors, thermostats, pressure switches etc.) - suitable for applications with separate delivery of control system; e.g. large buildings with central control system etc. 	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px; text-align: center;"> basic version (fans, actuators, thermostats, pressure switches and others on request) </div> <div style="text-align: center;"> ↑ ↓ </div> <div style="border: 1px solid black; padding: 5px; margin-top: 5px; text-align: center;"> Supervisory control system </div>
"RD5" controls	<p>Standard functions of the "RD5" controls</p> <ul style="list-style-type: none"> - EC fan speed control (based on selected mode) - automatic by-pass damper position (heat and cool recovery) - evaluates and prevents emergency limits based on measured temperature - ventilation and temperature weekly program setting - A web server and an Ethernet interface built in as standard connection for remote internet communication - inputs for switching using 230 V (4 inputs - 3 delayed, 1 instantaneous) - switch e.g. from bathrooms etc. - optional connection of CO₂ or RH sensor - max. 2 sensors with a switch or 0-10 V output - outputs for electric preheater and heater control (pulse 10 V) or hot-water control (0-10 V) <p>Additional RD-IO module</p> <ul style="list-style-type: none"> - optional manometer connection to ensure constant airflow control (see Constant airflow and pressure control on previous page) - constant pressure control - cooling control outputs (DX- or chilled-water cooling), possibly for a heat pump <p>Additional RD-K module</p> <ul style="list-style-type: none"> - additional inputs and outputs significantly extending control system functions <p>BACnet / KNX converter</p> <ul style="list-style-type: none"> - optional converter allowing connection to supervisory control system via BACnet or KNX protocol 	<p>CP Touch (touchscreen)</p>  <p>CP10RT</p>  <p>Web server (as standard)</p> 
"CPM" controls	<p>Standard functions</p> <ul style="list-style-type: none"> - EC fan speed control (stepless) - automatic by-pass damper position - frost protection of heat exchanger - switching of electric or water heater - input for external switch - inlet and outlet shut-off damper control - minimum and maximum fan speed preselection - analogue input (0-10 V) for air quality sensor (CO₂, RH) - outputs for controlling electrical preheater and heater (pulse switched 10 V) or water heater (controlled by 0-10 V signal) - outputs for controlling cooling (direct or water), eventually heat pump <p>Controller CPM</p> <ul style="list-style-type: none"> - fully graphic touchscreen - weekly program - „party“ mode - „holiday“ mode - filter change notice - automatic operation based on constant signal - e.g. constant pressure <p>Controller CP 10 RA</p> <ul style="list-style-type: none"> - rotatable controller 	 <p>CPM controller with touchscreen display</p>  <p>CP 10 RA with mechanical knob</p>